

Part Number PL-CHDMO-FC2



FEATURES:

- 1/3" CMOS Sensor
- Support Warm white (4000K), Light Distance : up to 25m
- Support OSD Menu
- Support DWDR
- Housing: Metal, IP67

±İŘŜ2 hdzúLJdzú a ZŘŜ	! İ 5κΦ±LY pa ΧητLJăkmnpFLJăŹ pa ΧολτLJăknpτLJăkmpτLJăŹ na ΧολτLJăknpτLJăτ / ±LY pa ΧολτLJăknpτLJăŹ na ΧολτLJăknpτLJăτ / ± . {
Camera	
LYI-ÊŜ {Ŝyă2Ų	мкођ / a h { {Ŝyă2Ų
LYI-ÊŜ wŜă2fdzúł2Y	pa Ynpfnfmfpn pa Ynpslfmfpn na Ymfnlfmлул
Φ± {ěăúŜY	t ! [kbΦ{ /
9tŜŌúŲ2yłŌ {KdzúúŜŲ	! dzú2
a lyYdy'LfddzYlyl'úł2Y	/ 2f2Ų Y лфло fdzĚ Χ CηλŹ л [dzĚ ōłŲK ōKłŲŜ ōĚKŲ
{Ōl-yŲlyŲ {ěăúŜY	tŲ2ŲŲŜăăłŌŜ {Ōl-y
Lens	
C2Ōdză [ŜyŲŲK	oΦcYŲ
C2Ōdză / 2yŲŲ2f	CİĚŜŘ
[Ŝyă ΦĚLJŜ	CİĚŜŘ
Night Vision	
Lw / dzú CİfúŜŲ	, 9{
lyŲŲŲŲŜŘ [95	bh , Suport Warm white (4000K)
Light Distance	up to 25m
IR Status	AGC Auto Control

Part Number PL-CHDMO-FC2

Camera Features	
Starlight	N/A
Day/Night	Color
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
Coaxial Audio	YES(only TVI)
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	
Housing	Metal, IP67
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 450mA
Dimension	∅ 96 x 91(H) mm
Weight	600g